Temperature Dependent Scintillation of Plastic Scintillators between 300 K and 4 K

Friday, 14 February 2025 10:15 (15 minutes)

Plastic scintillators are a common type of particle detector that is often used for their fast timing, robustness and cheap cost. Plastic scintillators are commonly used in veto systems since they can be made to large sizes needed for the experiment as well having a variety of dopants added to them to improve the detection of specific particles. As with any scintillator it is important to understand how the scintillator behaves in the environment that it will be in for the experiment. One consideration is the temperature that the scintillator will be operated at, specifically if the scintillator will be kept at cryogenic temperatures. Many inorganic scintillators have had their scintillation light yield determined at cryogenic temperatures, with many seeing an increase of up to 100% more (eg. http://link.aps.org/doi/10.1103/PhysRevB.84.214306). To generalize such tests to plastic scintillators, I present the results of an experiment that analyzes the light yield of EJ-200, a commercial plastic scintillator from Eljen Technologies, between 300 K and 4 K using α excitation from an 241 Am source. This study shows that the light yield decreases by 25% as temperature changes between 300 K and 4 K. Preparations for a similar experiment using Compton scattering of γ emissions from a 65 Zn source and a 137 Cs source are also presented.

Your Email

21nes8@queensu.ca

Affiliation

Queen's University

Supervisor

Philippe Di Stefano

Supervisor Email

distefan@queensu.ca

Your current academic level

PhD student

Primary author: SWIDINSKY, Nicholas (Queen's University)

Co-authors: ELLINGWOOD, Emma (Queen's University); Mr HUCKER, Jonathan (Queen's University); Prof.

DI STEFANO, Philippe (Queen's University)

Presenter: SWIDINSKY, Nicholas (Queen's University)Session Classification: Morning 2 - Particle Physics

Track Classification: Particle Physics